

Product Specifications

Product Information

| | |
|---------------------|-----------------|
| Product Description | Carnival |
| Stock Code | CAR* |
| Width | 138 CM |
| Weight (GSM) | 400 GSM |
| Weight (LM) | 552 Grams |

Composition & Construction

| | |
|--------------|----------------|
| Composition | 100% Polyester |
| Construction | Knitted |
| Backing | - |
| Yarn Count | - |
| Thread Count | - |

Performance Specifications

| | |
|----------------------------|---|
| Martindale Score | 80,000 Rubs |
| Furnishing Suitability | Severe Contract |
| Tensile Strength | - |
| Tear Strength | - |
| Pilling Resistance | - |
| Colour Fastness to Water | - |
| Colour Fastness to Rubbing | - |
| Colour Fastness To Light | - |
| Seam Slippage | - |
| FR Options (By Request) | Non-FR BS5852 Ignition Source 0 + 1 BS5852 Ignition Source 5 / Crib 5 |
| Water Resistance | Non-WR |
| Stain Resistance | Non-SR |
| UV Resistance | Non-UVR |

Care Instructions

| | |
|------------------------|---------------------------|
| Washing | Machine Washable to 40 °C |
| Ironing | Do Not Iron |
| Dry Cleaning | Do Not Dry Clean |
| Tumble Drying | Do Not Tumble Dry |
| Bleaching | Do Not Bleach |
| Special Considerations | - |

Origin

| | |
|-------------------|------------|
| Country of Origin | China |
| HS Tariff Code | 6006320000 |

Certifications

| | |
|-------------|----------------------------------|
| Oeko-Tex | OKEO-TEX® STANDARD 100, Class II |
| Fire Rating | On Request |

Notes

1. The information contained within this document is true and accurate to the best of our knowledge at the time of production (see above). Every effort will be made to correct any errors or inconsistencies as swiftly as possible. Any updated documents will be distributed through our website, or can be requested from a member of our sales team.
2. Any and all measurements may be subject to margins of error and/or manufacturing fault tolerances, and as such should be considered approximate. Subtle variations may occur between separate production batches.
3. Product specifications are no substitute for physical sample swatches, and should be used in conjunction with sample swatches to fully assess the suitability of any material for any particular end use. Customers themselves must make the final determination as to suitability.
4. If you have concerns as to the accuracy of any of the information presented in this document, please submit your enquiries in writing to: **info@ambassador-textiles.co.uk**.

BROWSE OUR WEBSITE

www.ambassador-textiles.co.uk

CONTACT US

+44 (0)161 624 4167

info@ambassador-textiles.co.uk

VISIT US

Unit A Vulcan Point, Vulcan Street, Oldham,
Greater Manchester, OL1 4DR